




Standard Module

5" Cell Module (160, 165, 170, 175, 180 Wp)

Features

- ◆ 72 pre-sorted high efficient mono-crystalline silicon solar cells
- ◆ Long term stability by quality control and exact tuning of components
- ◆ Non-overlapping bus bar design to lower risk of short
- ◆ Strict power measurement that minimizes the power tolerance to +/-3%
- ◆ Sorting limit of module classification to +/-2.5W
- ◆ Modules are manufactured in ISO 9001 and 14001 certificated facilities to guarantee prime quality as well as environment-friendly products

IEC certificate

The test sequences of the IEC 61215 and IEC 61730 confirm that Solar modules are capable of withstanding the artificial loads of the materials as well as safety qualification. It provides reliable performance and safety for entire range of Solar modules

REACH certificate

REACH Regulation (EC) No 1907/2006:

Article 7- Registration and notification of substances in articles

Article 33 - Duty to communicate information on substances in articles

Dimensions

Length * Width (mm)	1599*806
Thickness (mm)	40
Weight (kg)	15.8





Series 5" Cell Modules

Electrical characteristics under standard test condition (STC)¹

		160A E1	165A E1	170A E1	175A E1	180A E1
Maximum power (P _{max}) ²	W	160	165	170	175	180
Voltage at maximum power (V _{mp})	V	44.71	45.26	45.81	46.11	46.44
Current at maximum power (I _{mp})	A	4.51	4.64	4.76	4.85	4.94
Open-circuit voltage (V _{oc})	V	44.22	44.34	44.56	44.83	45.16
Short-circuit current (I _{sc})	A	5.13	5.05	5.13	5.21	5.31
Module efficiency	%	12.41	12.8	13.19	13.58	13.97

¹STC: AM1.5G, 1000W/m², cell temperature of 25 °C.

²Power tolerance at maximum power under STC condition = ±3%.

Temperature coefficient

Short-circuit current	α	Ts(I _{sc})	0.0248%/K
Open-circuit voltage	β	Tc(V _{oc})	0.2821%/K
Maximum power	γ	Tc(P _{max})	-0.3812%/K

Performance at low irradiance


** Module efficiency at 200 W/m², 25°C is lower than that at STC by approximately 0.4% (relative)

System Integration

** Maximum system voltage— 1000 V

** Fuse rating: 10A

Front View



Side View



Back View

