

Sun-Pursuit Pro Series

TOPCon
144 - cell Module

TW-600HTS-06

580-600W

0-3%Positive Tolerance



Monocrystalline




Half Cell



16BB



Grade A



• MODULE FEATURES



High efficiency

TOPCon technology improves efficiency, increases power generation, and contributes to lower LCOE.



Lower heat spot risk

Innovative circuit design and “Half Cell” structure decrease the temperature of heat spots and effectively reduce power loss.



Excellent low-light performance

Reliable performance in low-light conditions such as in the morning, at dusk or during raining days.



Resilient to extreme weather

Carefully selected materials ensure the module still works well under the condition of 2400Pa wind load and 5400Pa snow load.



PID resistant

High quality solar cell and advanced processing technology contribute to excellent PID resistance performance.


• Quality Certification



• Product Qualification



• Performance Warranty



12 Years Product Warranty




25 Years Linear Power Warranty

TW-600HTS-06

•Product Specification•

Cell Type	Mono crystalline
Cell Quantity	144 cell
Module Size (mm)	2278*1134*30
Module Weight (kg)	27.8
Glass Thickness (mm)	3.2
Frame Material	Anodized aluminum alloy
Junction Box	IP68
Cable/Connector	4mm ² , MC4compatible
Cable Length	+300mm/-300mm; or Customize
Max System Volt (V)	1500V DC
Max Fuse Rate (A)	30
Power Tolerance	0~+3%

•Engineering Drawings•



•Electrical Characteristics•

STC standard performance >>>

Power Level	580	585	590	595	600
Pmax(W)	580	585	590	595	600
Vmp(V)	44.11	44.28	44.46	44.64	44.81
Imp(A)	13.15	13.21	13.27	13.33	13.39
Voc(V)	53.03	53.24	53.46	53.68	53.89
Isc(A)	13.78	13.84	13.90	13.96	14.02
Module Efficiency(%)	22.44	22.64	22.83	23.02	23.22

NOCT standard performance >>>

Power Level	580	585	590	595	600
Pmax(W)	435	439	445	449	452
Vmp(V)	39.70	39.85	40.01	40.18	40.33
Imp(A)	10.96	11.01	11.06	11.11	11.16
Voc(V)	47.83	48.01	48.21	48.40	48.59
Isc(A)	11.60	11.65	11.70	11.75	11.81



STC: Irradiance 1000W/m², Module Temperature 25°C, AM1.5

NOCT: Irradiance 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s

•Temperature Characteristics•

Operating Temp (°C)	-40~85
Operating Humidity (%)	5~85
Hail Load Tolerance	25mm hailstone with velocity of 23m/s
Temp Coefficient (%/°C)	-0.29
Temp Coefficient Isc (%/°C)	0.046
Temp Coefficient Voc (%/°C)	-0.24
Operating Temp (°C)	44±2

•I-V Curve•



•Packaging Info•

Pieces per Pallet	36
Size of Packaging (mm)	2305*1125*1270
Weight of per Pallet (kg)	1026
Pieces per Container	720
Size of Container	40'HC



Add: No. 168, Group 8, Shangmanju, Caobu Town
Rudong County, Nantong City, Jiangsu Province, China
Tel: 86-513-69976081/81900128
Web: www.techwisesolar.com
Email: salesdept@techwisesolar.com

All data and specifications included in this brochure may subject to be modified without notice.
All Rights reserved by TechWise Solar Co.
(Sep 2025 V4 Edition)