

MonoPower Large Half Cells

ASP HM6L-60 Series 335W-345W

Monocrystalline PV-module



QUALITY & RELIABILITY

Best raw materials, optimized production process and accurate testing makes the quality difference



GERMAN ENGINEERING

Best design by the art of German engineering



SAVE INVESTMENT

Product warranty of 12 years
and performance warranty of 25 years



POSITIVE PERFORMANCE TOLERANCE

Up to +5 W plus-tolerance on output




FOR ALL ENVIRONMENTAL CONDITIONS

Resistant against PID, sand, salt and ammonia



STABLE AND STRONG

Capable to bear heavy snow loads up to 5400 Pa
and wind loads up to 2400 Pa




12 YEARS
PRODUCT WARRANTY

OUR PERFORMANCE GUARANTEE



25 YEARS

PERFORMANCE GUARANTEE



CERTIFICATES

SGS
TÜV
SAAR

IEC 61215
IEC 61730
PERIODICAL
INCEPTION


SGS

PID RESISTANT
SALT MIST RESISTANT
SAND RESISTANT
CORROSIVE GAS (NH₃)

CE CEC

Quality
Diligence
Durability

α SOLAR PLANET
Enjoy the quality difference



MonoPower Large Half Cells

ASP HM6-60L Series 335W-345W

TECHNICAL DATA

ASP335HM6-60

ASP340HM6-60

ASP345HM6-60

Maximum power	P _{max} (Wp)	335	340	345
Maximum power voltage	V _{mp} (V)	34.44	34.69	34.95
Maximum power current	I _{mp} (A)	9.73	9.80	9.87
Open-circuit voltage	V _{oc} (V)	41.61	41.88	42.23
Short-circuit current	I _{sc} (A)	10.22	10.30	10.38
Module efficiency	%	19.88	20.18	20.47
Power tolerance	P _{max} (W)	0/+5		
Maximum system voltage DC	V	1500		
Operating temperature	°C	-40 to +85		
Temperature coefficients of P _{max}	%/°C	-0.344		
Temperature coefficients of V _{oc}	%/°C	-0.272		
Temperature coefficients of I _{sc}	%/°C	0.035		
Nominal operating cell temp. (NOCT)	°C	44±2		

The electrical data apply to standard test conditions (STC): Irradiance of 1000 W/m² with spectrum AM 1.5 and a cell temperature of 25°C.


MATERIAL CHARACTERISTICS

Cell type	Monocrystalline 158.75 x 79.38 mm
No. of cells	120 (6 x 20)
Dimensions	1692 x 996 x 35 mm
Weight	19.0 kg
Junction box	IP68 rated
Output cable	4.0 mm ² , 350 mm length
Connector type	MC4 / MC compatible
Hail resistance	Max. Ø 25 mm, at 23 m/s
Wind load	2400 Pa / 244 kg / m ²
Mechanical load	5400 Pa / 550 kg/m ²

PACKING INFORMATION

Packing configuration	64 pcs / double pallet
Loading capacity	832 pcs / 40 HQ
Size / pallet	1725 x 1135 x 2400 mm
Weight	1336 kg / double pallet

DRAWINGS



Alpha Solar Planet GmbH
Döllgaststr. 4, 86199 Augsburg
GERMANY

Tel.: +49 821 99972360
Fax: +49 821 99972369

E-mail: sales@a-s-p.solar
Web: www.a-s-p.solar



© Alpha Solar Planet GmbH - All rights reserved - Errors and/or modifications excepted.